



# Ultrapure water for all systems



multidem

# A new generation of water demineralization units

Make the most of the many advantages offered by the installation of your new Multidem water demineralization system from W&H.



Multidem supplies top quality demineralized water for generating steam in autoclaves. As a result, it ensures consistent and optimized performance, thereby extending the

service life of your sterilizer or demineralization unit. In addition, the unit is also equipped with a spray gun and is ideal for rinsing instruments prior to sterilization.



## Very easy to operate and use



1.  
To replace a consumed filter cartridge, open the locking handle.




2.  
Turn the locking handle as far as it will go, then press the rinse button to release the pressure and take the filter head off the consumed filter cartridge.



3.  
Once you have pulled off the protective cap, place the filter head vertically onto the new cartridge. Multidem is then ready to go again!

# Compatible with all units

The water demineralization system is also suitable for use with many conventional autoclaves and demineralization units.



\* Applies to Lisa Fully Automatic units manufactured from 04/2011

## All advantages at a glance

### User-friendly

- > Fast cartridge replacement without tools
- > Cartridge can be positioned without a fixing/securing device

### Compatible

- > Suitable for use with conventional autoclaves and demineralization units
- > Flexible use in combination with the spray gun

### Economical

- > No external power supply required
- > Optimized ion exchange resin


### Safe

- > The purified water complies with the relevant recommendations and regulations for the operation of steam sterilizers and for the treatment and preparation of instruments
- > Consistently high water quality, no limescale deposits



# Technical data

Pictures are for illustrative purposes only. Additional equipment and accessories shown are not included as standard.

	Multidem C17	Multidem C27
Operating pressure:	2 bar – 8.6 bar (max.)	
Water temperature (inlet):	4 – 30 °C / 40 – 86 °F	
Nominal flow rate:	60 l/h	
Water quality (out):	demineralized (EN 13060)	
Water quality (in):	drinking water	
Weight:	1.7 kg	2.7 kg
Width/depth/height:	117 / 108 / 421 mm	124 / 123 / 476 mm
Operating position:	vertical	
Tube lengths:	2 x 3 m	
Safety valve:	yes	
Backflow preventer:		



Included with the Multidem C17	Included with the Multidem C27
Filter head	Filter head
Cartridge 1.7 kg	Cartridge 2.7 kg
Tubes and connectors (incl. Water Block®)	Tubes and connectors (incl. Water Block®)
Optional spray gun	
Spray gun	
Tubes and connectors	

If devices are connected downstream of the unit, make sure that appropriate steps are taken to prevent backflow in accordance with the guidelines, standards and regulations which are applicable in your country.

## Manufacturer:

W&H Sterilization Srl.  
Via Bolgara, 2  
24060 Brusaporto (BG), Italy  
t + 39 035-66 63 000  
f + 39 035-50 96 988  
office.sterilization@wh.com  
wh.com

